

# **GOLF CART BATTERY**

# DT866(8V150AH)


### 理工电池 LEOCH BATTERY


Physical Specification	
Nominal Voltage	8V
Nominal Capacity(20HR)	150Ah
Nominal Capacity(5HR)	125Ah
Length	260±2mm(10.24inches)
Width	180±2mm(7.09inches)
Container Height	248±2mm(9.76inches)
Total Height	279.5±2mm(11.00inches)
Dry Weight	Approx 19.7Kg(43.4lbs)
Wet Weight	Approx 26.5Kg(58.4lbs)
Acid	1.280±0.015g/cm³(25°C)
Standard Terminal	DT-M8(A)
Container Material	PP


# Rated Capacity 20 hour rate(7.5A) 150Ah 5 hour rate(25A) 125Ah Reserve Capacity 25Amps 225min 56Amps 90min


## **Discharge Characteristics(25℃, 77°F)** 6.4 6.0 Loading Voltage(V) 5.5 5.25 56A 25A 25A 5.0 4.5 4.0 5 10 30 60 2 3 10 **Discharge Time**











#### **Charge Method**

#### Initial Charge:

- $\bigcirc 10.1C_{20}(A)$  charging 15h
- 20.05C<sub>20</sub>(A) charging 10h

The temperature of the battery should be below  $50^{\circ}$ C during charging.

#### **Supplement Charge:**

- **a)**Charging at a constant voltage of  $9.8 \sim 10 \text{V/cell}$  and a limited current  $0.25 \text{C}_{20}$  (A) until the electrolyte density up to  $1.280 \text{g/cm}^3 (30 \,^{\circ}\text{C})$  and the current not change for 3 hours.
- **b)**Charge with constant current  $0.1C_{20}$  (A) until the voltage between  $10.4 \sim 11.2 \text{V/cell}$ , and voltage maintains for 3 hours and not change.

Two method optional