

Lithium Battery - Clean Manine Series



MKS-CP24150(25.6V150Ah)

Features Of LiFePO4 Battery

- Long cycle life
- High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection
- Capable of 1C fast charging

Application scenarios

- Push Floor Cleaning Carts
- Driving Floor Cleaning Carts
- Sweeping Carts



Specification

Nominal Voltage	25.6V
Working Voltage	20V-28.8V
Nominal Capacity	150Ah
Energy	3840Wh
Self Discharge	≤3% Per Month
IP Grade	IP65
Positive material	Lithium Iron Phosphate
Cell type	Square LFP
Weight	ABOUT 46.5KG
Dimension LxWxH	L526*W333*H223mm
Fixed size	/
Terminal Type	CNNT M8
Shell type	Powder Coated Steel
Handle	YES
Storage Temp. short term	-20~45°C
Storage Temp. long term	0~35°C
Cycle Life	3000 cycles
Heating function	NO
Cooling type	NO
Insulation	20MΩ/1000VDC, @25±5°C, RH50%

Charging

Rated Charge Current	50A
Upper limit Voltage	28.8V
Charging Temp. Range	0~55°C

DisCharging

Rated Discharge Current	100A
Max. discharge Current	300A(5S)
Rated Discharge Cut-off Voltage	22.4V
Min.Discharge Cut-off Voltage	>20V
Discharge Temp. Range	-20~60°C

Function (optional)

(CAN/RS485), Bluetooth, 4G, Screen, Charger

Physical Dimension-mm

